

# YDOC ML525

## 4G/5G Remote Telemetry Unit

**The YDOC ML525 is a remote telemetry unit designed specifically for environmental monitoring.**

The ML525 is a flexible, powerful RTU which feature a 4G/5G modem for transmission of data over the mobile data network. It features a world band modem that supports use of both Cat M1/LTE-M1 and NBIoT/NB1.

### YDOC ML525 RTU

The ML525 is compact and power efficient. Despite its small size it is packed with advanced features.

The RTUs feature 2 off pulse inputs, 2 off 4-20mA inputs, 2 off analogue voltage inputs as well as a Serial input which can be used with SDI-12 or MODBUS sensors (both RS232 and RS485). Readings are stored in 110MBytes of non volatile memory and a micro SD card of up to 16 GB can be added. The stored data can be manually downloaded. The standard form of data transfer is via automated FTP connection to the Sensori cloud server. But users can also nominate to send data via FTP, TCP, or MQTT to any platform of their choice. Alarms can be notified via Email or SMS. The log rates and data transfer rates are programmable over a wide interval. You can fit your own SIM or make use of the eSIM which has an included 500 MB data allowance.is

The advanced features in the ML525 include the ability to add calculated channels - which can combine values from any of the logged channels using a range of mathematical functions - as well as time based aggregation - allowing you to calculate average, maximum, minimum and total values for a period.

The RTU is programmed via a USB-C port. Sensor connections are made via cable glands or waterproof connectors.




### ACCESSORIES AND EXPANSION

The RTU's accessory port allows you to connect a range of additional devices, such as a Camera and Iridium Satellite modem. An expansion port allows the RTU capacity to be included further. By plugging in the required expansion board, users can add more analogue channels, bridge interfaces, differential amplifiers or additional serial ports.

### POWER OPTIONS

The ML525 may be fitted with a number of different covers, each which offers a different power supply option. The PV cover includes a 1W solar panel. The LFP option uses a 5W solar panel to charge a set of LiFePO4 (LFP) batteries. The DC-LI cover allows the unit to be powered by a single 13 AH 3.6 V lithium thionyl battery and the DC-3LI by up to 3 of these cells. The SLA charge board allows you to use a 3 to 30AH battery and 5 to 30W solar panel. If you have a requirement for a local display, the TFT cover provides a 2" TFT display which shows the latest sensor readings.



### Ordering

MLN525-xxx                      YDOC ML525 Remote Telemetry Unit with analogue SDI-12, MODBUS and pulse  
xxx= power option            PV, LFP, LI, 3LI, DC-AA, SLA

TOIP Pty Ltd  
58 George St MOONTA SA 5558 AUSTRALIA  
Email: sales@toip.au            Web: https://toip.au  
Phone: 08 8825 1208            Mob 04 9805 3413



**TOIP** Pty Ltd  
Telemetry Over Internet Protocols